# SAND KING







INTRODUCING THE ALL-NEW SAND KING.



# 01\_ SINGLE HOPPER DESIGN

Featuring 40° slope angles for quick and easy cleanout, the Sand King's single hopper was designed to keep you moving. For added convenience, a powered chute opener with remote control is available.

# 02\_ CHUTE OPENER

With an opening of 16" x 24", the rack and pinion chute opener operates the stainless steel trap door with ease. The trap door slides on a nylon wear strip supported by nylon rollers.

# 03\_ SEALED HOPPER

Loading the Sand King is easy and efficient with a remote-controlled power fill door on the top of the trailer. The fully sealed and enclosed hopper ensures that sand stays dry.

# 04\_ RIGID AND ROBUST DESIGN

The rigid steel subframe supports the structure of the trailer both at the front and rear. This robust design has durability in mind to provide years of trouble-free service.



### **BODY STRUCTURE**

| FRONT & REAR WALLS | Double Wall Construction, .063 Pre-Painted Aluminum Outside Skin, White or Black Colour Options c/w Access Ladders and Catwalk; Radius Corners; Other Options Available |
|--------------------|---|
| HOPPER CHUTES      | Standard Opening Size - 16" $\times$ 24"; Stainless Chute Shafts; 22 $\%$ " Clearance (w/ 11Rx22.5 Rubber)  |
| HOPPERS            | Single Hopper Trailer; Two-Piece Hopper Design; 40° Slope Angle; Double Row Stiffener On All Sides; Aluminum Chute Frame Huck-Bolted to the Opening                     |
| CHUTE OPENER       | All-Aluminum Frame; Stainless Steel Rack and Pinion Design; Stainless Steel Trap Door   |
| LANDING GEAR       | Jost Magnum Aluminum Landing Gear c/w 10" Cushion Foot; 10 Year Warranty  |
| LIGHTING           | Seven Wire Connector at Front; Truck-Lite LED Lighting Standard; Lifetime Warranty Lamps; Truck-Lite Wiring Harness; Other Options Available                            |
| MUD FLAPS          | $\ensuremath{\mathcal{V}}_2$ Rubber Anti-Sail Rear Flaps Standard; Other Options Available  |
| PAINT              | Three-Stage Paint Process Consisting of a Coating of Zinc, Urethane Primer and Top Coat (applicable to steel sub-assemblies)  |
| SIDE WALLS         | 68" Side Walls; Double Wall Construction, .063" Pre-Painted Aluminum<br>Outside Skin, White or Black Colour Options; Inside Finished; Other Options<br>Available        |
| SLOPES             | Aluminum Slope Sheets   |

### **RUNNING GEAR**

| AXLES        | Hendrickson INTRAAX .31" Wall, 5 $\%$ " Round, 71 $\%$ " Track, HN Spindle; Other Options Available  |
|--------------|--|
| BRAKE SYSTEM | Air Drum Brake Standard; H20 Brake Linings; Haldex 30/30 Gold Seal;<br>Haldex S-ABA Slack 5.5"; 28 Spline Standard; Wabco ABS Equipped; Other<br>Options Available |
| HUBS         | 10 Stud HP Cast Hub/Cast Drum Standard; Other Options Available  |
| SUSPENSION   | Hendrickson INTRAAX AANT23K LDA Air Ride Standard; Air Gauge<br>Mounted in an Aluminum Box c/w Window and Light. Other Options<br>Available.                       |
| TIRES        | Michelin/BF Goodrich Standard; Other Options Available   |
| WHEEL SEALS  | National   |
| WHEELS       | 22.5" Standard; Other Options Available  |





PRESTIGE TRAILERS

BOX 1146, 135 CANADA ST WINKLER, MB, CANADA, R6W 4B2

PHONE 1-866-797-0669 FAX 1-204-325-5369

PRESTIGETRAILERS.COM

Prestige Trailers is a brand of Triple E Canada Ltd. Product improvement is an ongoing process at Prestige Trailers.
Thus we reserve the right to change any specifications or components on any specifications or components on any or all products without prior notice; errors or omissions excepted. Prestige Trailers is under no obligation to units manufactured prior to changes in specifications. Printed in Canada 09/21